


SCIENCE & TECHNOLOGY OFFICE



Mag4: SEP Prediction


David Falconer, Igor Khazanov, Nasser Barghouty

Presentation, Sept 30, 2015



MAG4 Automated Processes





MAG4 is completely automated, from downloading magnetograms to outputting and storing forecast products.







- MAG4 (Magnetogram Forecast), developed originally for NASA/SRAG (Space Radiation Analysis Group), is an automated program that analyzes magnetograms from the HMI (Helioseismic and Magnetic Imager) instrument on NASA SDO (Solar Dynamics Observatory), and automatically converts the rate (or probability) of major flares (M- and X-class), Coronal Mass Ejections (CMEs), and Solar Energetic Particle Events
- MAG4 does not forecast that a flare will occur at a particular time in the next 24 or 48 hours; rather the probability of one occurring!
- GONG (<u>Global Oscillations Network Group</u>) magnetograms, can be used instead as a **backup** but at a lower forecast accuracy
- Present cadence of new forecasts: 96 minutes (60 minutes of CCMC)
 Vector magnetogram actual cadence: 12 minutes



MAG4 Background



- Flares and CMEs are known to be drivers of the most severe space weather
- Flares and CMEs typically originate in active regions (aka sunspots)
- Flares and CMEs are examples of exceptionally large explosive releases of magnetic energy stored in the corona
- While the amount of free energy cannot be measured directly, freeenergy proxies can be measured
- Event rates have been shown to be correlated with the magnitude of the free-energy proxies



R20 Timeline of MAG4



- 1973 The MSFC (Marshall Space Flight Center) vector magnetograph was built to support Skylab
- 2000-present MSFC used vector magnetograms to study CME correlation with freeenergy proxy
- 2007-12 A DOD/Multidisciplinary University Research Initiative/Neutral Atmosphere Density Interdisciplinary Research helped support funding of the basic research
- 2008 Partnered with JSC/SRAG (Space Radiation Analysis Group) and won an R20 NASA/Technical Excellence Initiative grant: Began building a database that grew to ~40,000 magnetograms of ~1,300 active region, covering years 1996-2004 with event catalog from SOHO/MDI (Solar and Heliospheric Observatory/Michelson Doppler Imager) observations
- 2010-present NASA's HEOMD (Human Exploration and Operations Mission Directorate) support
- 2010 SDO is launched began transitioning from MDI to HMI line-of-sight magnetograms.
- 2011 MAG4 installed at SRAG a <u>NRT (Near-Real-Time) forecasting tool</u>, and SRAG began pre-operations testing
- 2012 Provided NOAA web access to MAG4 NRT forecasts
- 2013 Improve MAG4 so that it can use a combination of free-energy proxy and previous flare activity
- 2015 Transition to HMI line-of-sight to vector magnetograms




Free-Magnetic Energy





Contours Vertical Magnetic Field Arrows Transverse Magnetic Field

Currents ~10¹² Amps












More



Twist



Size



Free Magnetic Energy Or Nonpotentiality




Process 2: Calculating the Free-Energy Proxy



- When the transverse gradient of the vertical (or line-of-sight) magnetic field is large, there is more freeenergy stored in the magnetic field
- For each Active Region:
 The integral of the gradient along the neutral line is the free-energy proxy

A magnetogram of an active region










Process 1: Identifying Active Regions



- Magnetograms are spatial maps of the magnetic field strengths
- They come in two basic types
 - line-of-sight (right)
 - vector magnetograms
- Free-energy proxies can be measured for Active Regions (areas with sunspots) from either type of magnetogram
- Line-of-sight magnetograms suffer reduced accuracy further from disk center




A full-disk line-of-sight magnetogram of the Sun, from SDO/HMI.

Magnetograms & identify ARs



Process 3: Converting Free-Energy Proxy to Predicted Event Rates





These empirical forecast curves are used to convert our free-energy proxy into predicted event rates. Curves are derived from a sample of 40,000 magnetograms, from 1300 active regions observed between 1996-2004.



Process 4: Forecast



Multiplicative uncertainty example


Rate 1 sigma Probability


Events/day 66% Confidence


0.02 0.01-0.05 0.7-5%

0.7 0.3-1.9 20-80%

For a Multiplicative Uncertainty of 2.7x







2012/03/06	3 14:23	
		!N Lng Lat
		(kG) (deg)
3 11428	9	-21 -17
5 11429	65	-41 17
6 11430	11	-25 20
1 11431	1	36 -27
	Disk Fore	cast Rates
Multip	olicative U	ncertainties
Disk All-Cl	ear Foreca	st Probabilities
	Uncer	tainties

24 H	lour Ev	ent Rat	:e		Dist
M&X	CME	FCM	E X	SPE	(deg)
0.020	0.020	0.009	0.002	0.003	27
0.700	0.400	0.200	0.100	0.080	44!
0.020	0.030	0.010	0.004	0.005	32!
0.000	0.001	0.001	0.000	0.000	45!
0.800	0.400	0.200	0.100	0.090	
2.7x 2	2.1x 2.	2x 3.0)x 2.4	X	
50.00%	% 7 0.00	0.08 %	00% 90	.00% 9	2.00%
40.00	% 20.0	0% 10.	00% 10	0.00%	7.00%



Comparison of Safe and Not Safe Days




June 26, 2013 C1, C1.5 flares

March 7, 2012

X5.4, X1.3, C1.6

CME 2684, 1825 km/sec,

Solar Energetic Proton Event reaches 6530 particle flux unit >10MeV






Improving the Forecasts:



1. Recent Flare History



Active regions that have recently produced an X- or M-Class flare are more likely to produce flares in the near future





2. Skill Metrics

Truth Table	Actual Yes	Actual No	PC POD	Percent Correct (0 to 100%) Probability of Detection (0 to 1)
Predict Yes	YY	YN	FAR	False Alarm Rate (1 to 0)
Predict No	NY	NN	HSS	Heidke Skill Score (-1 to 1)
			TSS	True Skill Score (-1 to 1)

Forecast Method	YY	YN	NY	NN	PC (%)	POD	FAR	HSS	TSS
McIntosh/NOAA	259	638	631	18476	93.7	0.29	0.71	0.26	0.26
Free-Energy Proxy	273	284	618	18830	95.5	0.31	0.50	0.35	0.47
Free-energy proxy and previous flare activity	340	317	551	18797	95.7	0.38	0.48	0.42	0.49
Best	890	0	0	19114	100	1	0	1	1





2. Skill Metrics Significance of Upgrade

Forecast Method	YY	YN	NY	NN	PC(%)	POD	FAR	HSS	TSS
McIntosh/NOAA	259	638	631	18476	93.7	0.29	0.71	0.26	0.26
Free-Energy Proxy Present MAG4	273	284	618	18830	95.5	0.31	0.50	0.35	0.47
Free-energy proxy and previous flare activity Upgraded MAG4	340	317	551	18797	95.7	0.38	0.48	0.42	0.49
Best	890	0	0	1911 4	100	1	0	1	1


Improvement in Metric	PC(%)	POD	FAR	HSS	TSS
McIntosh/NOAA Present MAG4	1.8±0.5	0.03±0.05	0.21±0.07	0.10±0.04	0.21±0.07
	(4σ)	(0.3σ)	(3σ)	(2σ)	(3σ)
Present MAG4 Upgraded MAG4	0.2±0.2	0.08±0.03	0.02±0.05	0.06±0.03	0.03±0.05
	(0.7σ)	(2σ)	(0.5 σ)	(2σ)	(0.5 σ)





1. Situational Awareness

- During periods when flare-productive active regions cross the disk, the predicted rate and actual rate both increase, providing situational awareness
- The results are best when flares and predicted rates are limited to inner 45 degree circle (Right)






MAG4 Improvements: Vector Magnetograms




Both vectors shown in red have positive B_z (magnetic field out of the sun), but have opposite sign B_{LOS} and thus a false (unphysical) neutral line in the line-of-sight (LOS) field.



Actual Examples

False Neutral
Lines occur on
limbward sides of
sunspots.

Problem fixed by converting from B_{LOS} and B_{Transverse} to B_Z and B_{Horizontal}





Process 1: Identifying Active Regions



- Magnetograms are spatial maps of the magnetic field strengths
- They come in two basic types
 - line-of-sight (right)
 - vector magnetograms
- Free-energy proxies can be measured for Active Regions (areas with sunspots) from either type of magnetogram
- Line-of-sight magnetograms suffer reduced accuracy further from disk center

06-Mar-2012 14:23 **Best LOS** Accuracy NOAA Active Regions (ARs) Best Vector Accuracy?

A full-disk line-of-sight magnetogram of the Sun, from SDO/HMI.

Magnetograms & identify ARs



Vector Version





Improvements with Vector MAG4



- Correct for systemic errors in measurements due to radial dependence of transverse field noise and foreshortening.
- Access skill scores relative to present LOS
- Investigate if a vector measure is better than LOS measure
- Investigate if change of measure is important
- Investigate if combination produces better measure
- Correct SPE forecasts based on Longitude of source region
- Partner with heliosphere modeling to better forecast where the particles would go.
- Twin CME



BACKUP







Basic Research to do for later R20



 Determine if growth/decay phase of an active region has additional prediction ability



 Determine if looking at twin-CME or single-CME can produce improved SEP forecasts







2. Skill Metrics Equations

	Actual Yes	Actual No
Predict Yes	YY	YN
Predict No	NY	NN

Metric Equations

Percent Correct PC=(YY+NN)/(YY+YN+NY+YY)

Probability of Detection POD=YY/(YY+NY)

False Alarm Rate FAR=YN/(YY+YN)

Heidke Skill Score HSS=2*(YY*NN-YN*NY)/[(YY+NY)*

(NY+NN)+(YY+YN)*(YN+NN)]


True Skill Score TSS=(YY*NN-NY*YN)/((YY+NY)*(YN+NN))



Today's Forecast

Questions








Research to Operations and Operations for FY14




- Continue to supply support, and upgrades to NASA/SRAG
- Finish and evaluate using vector magnetograms
- Fully implement in consultation with SRAG using combined free-energy proxy and previous flare activity
- Improve All Clear Forecast for SEP
- Partner with Air Force, and through them NOAA





How Free Energy Proxy Evolves and Clustering of Flares





The free-energy proxy evolves on time periods of days => the forecast is on those time scales




Improving the Forecasts:



2. Vector Magnetograms (In Progress)

- MAG4 presently uses SDO/HMI line-of-sight magnetograms
- Near-real-time ambiguityresolved SDO/HMI vectormagnetograms have recently become available
- We are transitioning to using these new data from SDO
- Implementation just started





How well it works (All-Clear)



Flares occur when high free-energy proxy active regions crossing disk.

